

# SPEED DOME

Day & Night



Dôme antivandale spécial embarqué pour toute application gouvernementale / militaire. Produit pouvant être fixé sur plafond ou toit, grâce à son système unique d'inversion d'image vertical et horizontal.

Vitesse de rotation allant jusqu'à 400°/s (mode preset). Ce produit est idéal pour une surveillance en temps réel grâce à sa vive réactivité traduite par sa vitesse de rotation.

## Features

- 480 TVL HIGH Resolution
- 0.002 Lux Minimum Illumination
- 23x Optical Zoom, 10x Electronic Zoom
- Built in MOLPF switching Mechanism for increasing Sensitivity color and monochrome
- Lens No Focus Shift (Built in MOLPF)
- On Screen Display Manual
- High Speed Pan 400°/sec, Tilt 330° /sec
- Auto-Flip
- Built In 4 Alarm Inputs / 1 Outputs
- A total of 128 points can be set for monitoring with smart auto tracking
- Camera with standard encoding of up to 256 units
- Remote control through infrared or RS-485 Interface
- The certified blast proof and reinforced-coated spherical hood and the rigid aluminum alloy waterproof casing makes it apt for both indoors and outdoors
- This product has earned various patents for its exclusive design. It is safe to use
- Approval: CE, FCC, IP66 (IEC529)

## PTZ-026WC



**ALLWAN-SECURITY**  
tel : +33 2 41 35 01 25

## SPECIFICATIONS

Modèle	PTZ-026WC
Module	1/4" COLOR SONY CCD (Day & Night) EXVIEW HAD
Sync System	Internal synchronous
Resolution	480 TVL
Effective Pixels	PAL : 470K Pixel
Sensitivity	EXVIEW HAD CCD: 0.1 Lux (Color) / 0.02 Lux (B/W) / 0.002 Lux (SU)
Lens	23x Zoom lens f 3.6~82.8mm / F 1.6~3.8
Electronic Zoom	10x Digital zoom
S/N Ratio	50dB (AGC OFF)
IR-Cut Filter	Auto / Manual
Focus	Auto / Manual
Electronic shutter	NTSC:1/60 ~ 1/100,000 Sec. / PAL:1/50 ~ 1/100,000 Sec.
Video output	1.0 Vp-p, 75Ω
$\alpha$ Correction	0.45 / 1
Gain Control	Super AGC 0 ~ 36dB
White Balance	ATW 2500° ~ 9500°K Preset / Manual
BLC	Super BLC / 48 zone BLC
OSD Function	OSD Menu
Rotation mode	Auto Pan Feature / Preset Position Patrol / Auto-Flip
Rotation angle	Horizontal Pan 0° ~ 375° / Vertical Tilt 0° ~ 95°
Rotation speed	Horizontal Pan 400°/sec / Vertical Tilt 330° /sec
Speed setting	Auto: Approx. 2.5~60°/sec(Variable) / Manual: Approx. 2.5~160°/sec(Variable) / Preset: Max. 320°/sec
Stop times	5 ~ 255 Sec (Variable)
Alarm inputs	4 inputs
Alarm outputs	1 output
Preset	128 Points
Control	Infrared Remote Control + RS-485 Control
Max link	256 Cameras
Protocol	DYNA 9600, ELITAR 2400, CHIPER 9600, LILIN 9600, PELCO-D 2400, PELCO-P 4800, PELCO-P 9600
Power supply	DC13.5V / 2.0A
Ambient Operation	0°C ~ 50°C / 30% ~ 90% RH
Blower / Heater	
Installation location	Indoor / Outdoor Ceiling mounted Wall mounted with Bracket (SPD-301)
Cover	Rugged dome
Material	Aluminum alloy IP66 waterproof casing ABS fireproof Fiberglass
Dimensions	Ø186 x H142mm
Weight	2.3Kg
Approval	CE, FCC, IP66 (IEC529)

© Specifications subject to change without notice. v1.1



**Allwan - Security**  
tel : +33 2 41 35 01 25