

# PTZ-026WC-DN

## Specifications

Pick-Up Device	Sony Exview HAD Color CCD
Resolution	480TV Lines (Color Mode) 600W Lines (B&W mode)
Sensitivity	0.1 Lux (Color) 0.01 Lux (B&W Mode) 0 Lux IR illumination
Lens	230x zoom(23xopt. IOx digital)
IR-Cut Filter	Auto/Manual
Rotation Mode	Auto Pan Feature/Preset Position Patrol
Rotation Angle	Horizontal Pan 0-375° Vertical Tilt 0—90°
Rotation Speed	Horizontal Pan 100°/s Vertical Tilt 100°/s
Speed Setting	Auto:Approx 5~60/s(variable) manual: Approx 5~90/s(variable) Preset: Max. 100/s
Max Link	64 Cameras
Preset	128 Points
Control	Remote Control & RS-485 Control
Dimensions	186XH135mm(7.3"xH3")
Weight	Approx 2.2Kg
Power Supply	DC12V/1.0A
Temperature Operation	10°~60° Less than 10%~90% humidity

Function	Speed Dome Controlling Functions
Pan/Tilt	Move joystick or press the direction keys left/right and up/down.
Enter Programming Menu	Enter [MENU] or setup Preset 95 or 64
Start Auto Tour	Call Preset 76 or 61 or Press key [Tour] (Refer to Controlling System Manual)
Stop Tour	Press key [Tour] again.
Start Auto Scan	Call Preset 99 or 60 or Press key [Scan] (Refer to Controlling System Manual)
Scan Limits	Left Limit: Setup Preset 92 or 62 Right Limit: Setup Preset 93 or 63
Stop Scan	Press key [Scan] again.
Auto Flip	Program the on/off in the menu.
Zoom in	Press [zoom tele] or turn the joystick clockwise until the desired view occurs or limitation reached.
Zoom out	Press [zoom wide] or turn the joystick counter-clockwise until the desired view occurs or limitation reached.
Focus Far	Select Auto/Manual in the menu. (refer to Menu Edit Manual )Under the Manual mode, please press [FOCUS FAR] till the view is clearly. The manual control will be invalid under the Auto mode.
Focus Near	Select Auto/Manual in the menu. (refer to Menu Edit Manual )Under the Manual mode, please press [FOCUS FAR] .till the view is clearly. The manual control will be invalid under the Auto mode.
Preset	Max 128 presets (Refer to Controlling System Manual)
Privacy zone asking	Can program max 8 units zone in current vision to protect privacy, and store in presets. This function is in regard to the selected camera. (For SONY480BP, SONY45BP, HITACHI454 and HITACHI274) (Refer to Menu Edit Manual)
Preset Title	Refer to description of Menu Edit Manual
Camera Title	Refer to description of Menu Edit Manual
Proportional Curve character	The manual control to the pan and tilt will be limited when the It is useful when proportion is on. (Refer to description of Menu Edit Manual). The speed of pan/tilt will be comparatively slower at wide photo zoom settings to ensure an accurate catching function. The mm. speed is 2° /S. It doesn't affect the preset call and tour function. Before the function on, speed under the manual controlling does not relate to camera zoom.