



## ANC-808V Pan/Tilt/Zoom Internet Camera



### Specification

#### System

CPU: Trimedia PNX1300  
RAM: 16MB SDRAM  
ROM: 4MB FLASH ROM

#### Networking

##### Protocol

TCP/IP, HTTP, SMTP, FTP, Telnet, NTP, DNS and DHCP

##### Physical

10BaseT Ethernet or 100BaseT Fast Ethernet

#### Audio

32Kbps, 24Kbps, 8Kbps  
Acoustic echo cancellation  
Full duplex audio communication

#### Camera Speciaifaction

1/4 inch color CCD sensor  
704x480 or 704x576  
Typical: 1.5 Lux / F1.8  
AGC, AWB  
Electronic shutter: 1/60(1/50) to 1/120,000 sec

#### Lens

Focal length 4.2~42mm  
Aperture F1.8~2.9  
10X digital zoom  
10X optical zoom

#### Video

##### Algorithm Supported

MPEG4 SP and JPEG

##### Features

Adjustable image size, quality and bit rate  
Timestamp and text overlay  
3 motion detection windows

##### Resolution

Up to 30/25 frames at 176x120 or 176x144  
Up to 30/25 frames at 352x240 or 352x288  
Up to 15/12 frames at 704x480 or 704x576

#### Microphone

Omni-directional  
Frequency: 20 – 20,000Hz  
S/N ratio: more than 58dB

## Power

Consumption: MAX 12W  
Universal switching power-supply included  
Adapter input: 100-240VAC, 50/60Hz, 0.4A  
Adapter output: 12VDC, 1.5A

## Operating Environment

Temperature: 0-40°C/32-104°F  
Humidity: 85%RH

## EMI & Safety

CE, FCC

## Viewing System Requirement

### Operating System

Microsoft Windows 98SE/ME/2000/XP

### Browser

Internet Explorer 6.x or above

## General I/O

1 sensor input(max. 12VDC 50mA)  
1 relay output(max. 24VDC 1A, 125VAC 0.5A)

## LED Indicator

Dual color system status indicator

## Dimension

104.5mm(L) \* 104.5mm(W) \* 125mm(H)

## Weight

NET. 420g