



DOME IP AICA 500

CARACTERISTIQUES

Model	ICA-500
Hardware	
Sensor	
Iris control	Video-drive iris control
Gain control	High/Low switchable
White balance	Indoor, auto mode (color temperature: 2500K~9000K)
Focus	or Fixed, lens length=3.6mm, manually fine tune
Minimum Illumination	0.2LUX@F2.0
PAN (Horizontal Rotation)	0°~325°
Tilt (Vertical Rotation)	10°~90°
Network	1 x 10/100Mbps RJ-45 port Generic
I/O port	2 x I/O ports, one for input and one for output
Video interface	BNC connector for monitoring
Audio interface	Built-in microphone for audio recording
Image (Video setting)	
Image compression	JPEG, 3 levels
Video Resolution and Frame Rate	640 x 480 (20fps), 352 x 288 (30fps), 320 x 240 (30fps), 176 x 144 (30fps)
Image Rotate	Rotate 0, Rotate 180, Flip Horizontal, Flip Vertical (note: the recorded video will not be rotated)
Environment	
Operating Temperature	5~45 degree C, 10~80% humidity
Power Requirement	12V DC
EMC/EMI	CE, FCC Network and Configuration
Connection type	Static IP, PPPoE, DHCP
Management	Web, CamView camera utility



ALLWAN SECURITY

Tél : 0 825 600 625

Mail : info@allwan.fr