



**ALLWAN SECURITY**  
www.allwan.fr

Speed Dome

**AU-G60-S/W**  
INTELLIGENT  
HIGH-SPEED DOME  
CAMERA SERIE

## High lights



Aluminum Construction



Sony Original  
Zoom Camera



IP66 Water-proof



Multi-protocol Setting

### SPECIFICATION CAMERA/OPTICS

Model	AU-G60-SB26	AU-G60-SB18	AU-G60-SC18
	AU-G60-WB26 Day/Night	AU-G60-WB18 Day/Night	AU-G60-WC18
Signal Format		PAL / NTSC	
Scanning		Progressive	
Image Sensor		1/4 inch Ex-View CCD	
Horizontal Resolution		470 TVL, 440K Pixels (PAL)	
Viewing Angle	54.2° (Wide end) 2.2° (Tele end)	48.0° (Wide end) 2.8° (Tele end)	48.0° (Wide end) 2.8° (Tele end)
Lens / Digital Zoom	26x Opt./12x digital	18x Opt./12x digital	18x Opt./12x digital
Min. Illumination	Day:2.0Lx(1/50),0.14Lx(1/4) Night:0.7Lx(1/50),0.05Lx(1/4)	Day:0.7Lx (1/50), 0.1Lx (1/4) Night: 0.01Lx (1/4)	0.7 Lux (1/50 sec., Color)
Focus		Auto / Manual	
White Balance		Auto / Manual	
Shutter Speed (PAL)		1 to 1/10,000 sec.	
Iris Control		Auto / Manual	
Gain Control		Automatic / Off	
Video Output		1.0 Vp-p, 75 Ohm	
S/N Ratio		More than 50dB	
Pan Speed		0.5° - 300° per Sec.	
Tilt Speed		0.5° - 150° per Sec.	
Pan Range		360°	
Tilt Range		0 - 90°	
Communication		RS-485, multiple-protocol	
Preset Positions		80 Presets	
Auto Pan		Yes, between 2 presets	
Tour / Sequence		4 progr. Tours / 4 Pattern	
Alarm inputs		4 inputs / 1 output	
Operating Temperature		Indoor: -10°C to 40°C	
Power Consumption		24V AC / 24-40 VA	