

## ENREGISTREUR NUMERIQUE CPD500W



### Features

MODEL	CPD 500W	CPD 500
R.E.T.R. (Remote Event Trigger Recording) Function	●	—
MPEG-2 compression format	●	●
USB Backup	●	●
Multiplex function (record and playback)	Triplex	Duplex
Advanced Motion detection function	●	●
DVD image quality	●	●
4 times resolution than MJPEG	●	●
Remote Control via Internet.	●	Via Video Web Server
Auto e-mail warning system & images uploading function (to FTP site).	●	—
Multi AP screens and HTTP display (IE browser) supported.	●	—
High resolution: 720x480pixels<NTSC> 720x576 pixels <PAL>.	●	●
Picture-in-Picture (PIP) function	●	●
Alarm input & output function	●	●
Video loss detection on each channel	●	●
2X digital Zoom	●	●
Recording rate: Up to 30 frames/sec (NTSC) ; Up to 25 frames/sec (PAL).	●	●
Support 1 HDD, IDE TYPE	●	●
Quick multiple search by time/event	●	●
Security password protection	●	●
●= Yes, —= N/A.		

## Specifications

MODEL	CPD 500W	CPD 500
Video Format	NTSC/EIA or PAL/CCIR	
Hard Disk Storage	IDE type, UDMA 66, support over 250 GB HDD	
Network Interface	Ethernet (10/100 Base-T)	—
Protocol	TCP/IP, ICMP, SMTP, HTTP, FTP	—
Remote Control	●	—
Trigger & Action	E-mail images or images uploading to FTP account / Remote Recording	—
Recording Mode	Manual / Timer	
Main Monitor Input	Composite video signal 1 Vp-p 75Ω BNC, 4 channels	
Main Monitor Output	Composite video signal 1 Vp-p 75Ω BNC	
Call Monitor Output	Composite video signal 1 Vp-p 75Ω BNC	
Motion Detection Area	16 x 12 targets per camera	
USB Interface	1 port. Support USB 1.1 Device	
Motion Detection Sensitivity	16 Levels	
Video Loss Detection	Yes	
Refresh Rate	Up to 120 frames/sec. for NTSC; 100 frames/sec. for PAL	
Recording Rate	Up to 30 frames/sec. for NTSC; 25 frames/sec. for PAL	
Dwell Time	Programmable (1~24 Sec)	
Picture in Picture	Yes (Movable)	
Key Lock	Yes	
Picture Zoom	2 x 2 (Movable)	
Alarm Input	TTL input, High (5V), Low (GND)	
Alarm Output	COM./N.O./N.C	
Time Display Format	YY/MM/DD, DD/MM/YY, MM/DD/YY, OFF	
Power Source	DC 19V	
Power Consumption	<32W	
Operation Temperature	10°C ~ 40°C	
Dimension (mm)	343(W) x 223(L) x 59(H)	
Net Weight	2 kgs (W/O HDD)	
●= Yes, —= N/A.		



**ALLWAN SECURITY**

Tél. 0825 600 625

Web : [www.allwan.fr](http://www.allwan.fr)

Mail : [info@allwan.fr](mailto:info@allwan.fr)